

NOZZLE PIPE CLAMP HOLDERS

QUICK RELEASE NOZZLE HOLDERS FOR ANY SPRAYING APPLICATION



APPLICATION

Pre-treatment
Washing Vehicles
Industrial Washing Machines
Washing Metals
Degreasing
Washing printed circuit boards

FEATURES

Nozzle Orientates 54 degree in any direction
Max Operating pressures 10 bar
Nozzle can be aligned by hand and changed quickly
Quick set-up system features 'snap in' tips
Pipe sizes 1/2" NB to 1 1/2" NB

DESCRIPTION

These nozzle pipe clamp holders are ideal for a large number of applications due to its quick release design. Nozzles can be changed quickly and aligned by hand without tools. These holders make maintenance easier as the nozzle tip is easily accessible.

MATERIALS AVAILABLE

Polypropylene
PVDF

NPT OR BSP CONNECTION	PIPE SIZE	DIMENSIONS						
		D	BR	B1	B2	B3	H1	H2
3/8" BSP	1/2"	20.22	6.2	21.2	23.8	18.5	36.5	16.5
3/8" BSP	3/8"	16.5-18.0	6.2	19.0	22.0	18.5	34.5	14.5
3/8" BSP	3/4"	25-27.5	7.8	24.5	26.5	22.0	39.5	17.5

HOLDERS FOR PIPE SIZES 3/4" – 1 1/2" NB			DIMENSIONS		
THREADED BALL CONNECTION	PIPE SIZE	SPIGOT SIZE	A	B	C
1/8", 1/4" 3/8" NPT	1"	10, 14, 17MM	62	39	67
1/8", 1/4" 3/8" NPT	1 1/4"	10, 14, 17MM	67	43	72
1/8", 1/4" 3/8" NPT	1 1/2"	10, 14, 17MM	71	46	75

