# STAINLESS STEEL ROTATING SPRAY HEADS



# DESCRIPTION

These stainless steel rotating spray heads are designed to rinse and clean tanks and vessels up-to 20metres in diameter. They are designed to meet the required standards needed for a wide range of industries such as Chemical, Dairy, Food and Beverage.

The high quality design allows for high performance cleaning efficiency while helping to extend operating life and reduce life cycle costs.

ORDERING EXAMPLE RSB 65-Stainless Steel

#### **APPLICATION**

Tanks and vessel up-to 20 meter in diameter

#### **FEATURES**

Self-cleaning, Media Lubricating

Designed for use when high impact cleaning is required Ideal for large tanks where the products is difficult to clean

360° wash patterns
Variable cycle times
Female connections
High impact jets
Minimum moving parts, to ensure extended operating life and reduce downtime
Working pressure 3 – 12 bar
Max working temp 95° C

# ROTATING SPRAY HEADS FOR TANKS AND VESSELS UPTO 20 METRES

### Up to 3 Metre Diameter Spray

RSB Model	RSB45		RSB45i		RSB65		RSB65i		
Pressure Bar	Flow lpm	Max Clean Radius m							
1.0	66.00	1. 15	76.67	1.35	166.67	1.95	183.33	2.4	
1.5	80.00	1.2	93.34	1.4	200.00	1.97	225.00	2.42	
2.0	88.33	1.25	110.00	1.45	241.67	2.0	266.67	2.45	
2.5	103.33	1.25	121.67	1.43	266.66	1.97	300.00	2.44	
3.0	106.67	1.2	126. 27	1.42	291.67	1.95	325.00	2.43	

# Up to 20 Metre Diameter Spray

Supply Pres KG/cm <sup>2</sup>	4 x 5mm		2 x 6mm		2 x 7mm		4 x 8mm		2 x 10mm		2 x 12.5mm	
	Flow lpm	Jet lgth m	Flow lpm	Jet lgth m	Flow Ipm	Jet lgth m						
5	156.66	1.9	105.00	6.5	135.00	7.8	333.33	9.0	290.00	13.0	440.00	13.0
6	173.33	5.5	118.33	7.1	153.33	8.5	366.67	9.9	320.00	14.5	480.00	15.0
7	185.00	6.4	130.00	8.0	166.67	9.5	393.33	10.6	350.00	16.0	520.00	17.0
8	195.00	7.3	138.33	9.2	180.00	10.4	416.67	11.2	370.00	17.5	550.00	18.5
9	201.66	8.5	146.66	10.2	191.67	11.5	440.00	12.2	390.00	19.0	580.00	20.0
10	206.67	9.0	153.33	11.5	200.00	12.5	458.33	13.0	403.33	20.0	591.67	21.0